Title	NESP Biodiversity Hub Hunter Marine Park Towed Video Imagery	
Alternative title(s)	NESP Biodiversity Hub D3 Project: still imagery of the seabed in the Hunter Marine Park	
Abstract	Raw downward facing still imagery of the seabed for Hunter Marine Park acquired using NSW Department of Planning Industry and Environment towed video system aboard RV Bombora for the National Environmental Science Program (NESP Biodiversity Hub). Fieldwork was funded, both cash and in-kind, by NSW DPIE and NESP in Year 5 (2019) of the program for 8-10 days of towed video over areas surveyed earlier in the program using a multi-beam echosounder (MBES) in 2015-16 and 2018-19 (NSW DPIE). A report titled 'Mapping and characterising the rocky reef habitat, fish and sessile invertebrate assemblages of the Hunter Marine Park' is available on the NESP website. Sites were randomly selected across mapped areas of the park's inner shelf, >3NM offshore of Seal Rocks, Broughton Island and Outer Gibber and covering depths of ~25-110m. Georeferenced (XYZ)and time-stamped (UTC) still imagery is accessible via DPIE Information Asset Register (IAR) and NSW Sharing and Enabling Environmental Data (SEED) website and linked to the online annotation platform Squidle+.	
Resource locato	r	
<u>Data Quality</u> <u>Statement</u>	Name: Data Quality Statement	
	Protocol: WWW:DOWNLOAD-1.0-httpdownload	
	Description:	
	Data quality statement for NESP Biodiversity Hub Hunter Marine Park Towed Video Imagery	
	Function: download	
Unique resource	identifier	
Code	c16ffe39-fb1d-4ace-8a6f-efa73a4939a6	
Presentation	Image digital	
form		
Edition	1	
	1 English	
Edition Dataset	English	
Edition Dataset language	English	
Edition Dataset language Metadata standa	English	
Edition Dataset language Metadata standa	English ard ISO 19115	
Edition Dataset language Metadata standa Name Edition	English ard ISO 19115 2016	
Edition Dataset language Metadata standa Name Edition Dataset URI	English ard ISO 19115 2016 https://datasets.seed.nsw.gov.au/dataset/c16ffe39-fb1d-4ace-8a6f-efa73a4939a6	
Edition Dataset language Metadata standa Name Edition Dataset URI Purpose	English ard ISO 19115 2016 https://datasets.seed.nsw.gov.au/dataset/c16ffe39-fb1d-4ace-8a6f-efa73a4939a6 baseline for monitoring	

Code identifying the spatial reference system

4283

Spatial resolution	1 m
Additional information source	Data were collected on 7-9 separate dates during the time period to acquire imagery once from each for the randomly selected locations identified at the start of the survey.
Topic category	

Keyword set			
keyword value	MARINE-Biology		
	MARINE-Coasts		
	MARINE-Reefs		
	PHOTOGRAPHY-AND-IMAGERY-Remote-Sensing		
Originating controlled vocabulary			
Title	ANZLIC Search Words		
Reference date	2008-05-16		
Geographic location			
West bounding longitude	152.352905		
East bounding longitude	152.653656		
North bounding latitude	-32.619714		
South bounding latitude	-32.428658		
NSW Place Name	Port Stephens Great Lakes Worimi		
Vertical extent information			
Minimum value	-100		
Maximum value	2228		
Coordinate reference system			
Authority code	urn:ogc:def:cs:EPSG::		
Code identifying the coordinate reference system	5711		
Temporal extent			
Begin position	2019-10-20		
End position	N/A		
Dataset reference date			
Resource maintenance			
Maintenance and update frequency	Unknown		
Contact info			
Contact position	Data Broker		
Organisation name	NSW Department of Climate Change, Energy, the Environment and Water		
Telephone number	131555		
Email address	data.broker@environment.nsw.gov.au		
Web address	https://www.nsw.gov.au/departments-and-agencies/dcceew		
Responsible party role	pointOfContact		

Lineage

Video surveying was undertaken following the recommendations detailed in 'Field Manuals for Marine Sampling to Monitor Australian Waters' (https://www.nespmarine.edu.au/field-manualsmarine-sampling-monitor-australian-waters). Details of the NSW DPIE towed video system and equipment are provided in 'SeaBed NSW: Standard Operating Procedures of multibeam surveying' (https://www.environment.nsw.gov.au/-/media/OEH/Corporate-Site/Documents/Research/Our-science-and-research/seabed-nsw-standard-operatingprocedures-multibeam-surveying-190101.pdf). XYZ positional accuracy of the still imagery is better than XY (3 degrees of slant range [eg. 2.6m radius @ 100m]; <1m POS MV GPS G2 and POS to USBL offset) and Z (~0.2m based on USBL and tow-fish camera P-sensor with 0.54m offset). Imagery was obtained during the period 21 October 2019 - 31 October 2020 using a DSLR still camera (Towed Digital Stills - TDS) and forward looking live-feed (fibre) video (Towed Digital Video - TDV). TDS were captured at 2s intervals along 80-90 x 200m transects and characteristically ~1m from the seabed with dual green lasers (spaced 100mm) for measuring seabed distance (horizontal). TDS were re-labelled using NSW DPIE naming convention (NSWDPIE TDS NESP Hunter Location_Site_transectnumber_Dateyyyymmdd_TimeUTChhmmss). Image (JPG) time-stamping in UTC extracted from associated EXIF (Exchangeable Image File Format) metadata; Transect metadata file (CSV) for each transect contains the following columns: 1) Filename (as above); 2) Timestamp yyyy-mm-dd hh:mm:ss in UTC; 3) Latitude_TDS (Y GPS coordinate of TDS from USBL); 4) Longitude TDS (X GPS coordinate of TDS from USBL); 5) Depth TDS (Z stills camera depth in metres = derived from Pressure-sensor on TDV + physical offset TDS to TDV Pressure-sensor (0.54m); 6) Latitude Ship (vessel Y coordinate); 6) Longitude_Ship (vessel X coordinate); 7) Sounder_Ship (raw vessel depth sounder output in metres); 8) COG_Ship (vessel heading in degrees); 9) SOG_Ship (vessel speed over ground in knots); 10-12) Roll SHIP, Pitch SHIP, Yaw SHIP of Ship; 13) Depth USBL (Z offset calculated from USBL transponder to transceiver using slant range); 14) Bearing USBL (direction from vessel to USBL in degrees); 15) Flag (Numerical data flag of range 1 - 3 indicating source of positional data, method outlined in 'Absolute External Positional Accuracy', NaN = True fish position). Image and image metadata records (generated in csv format) were uploaded to NSW SEED Amazon Web Service for access and annotation in Squidle+.

Limitations on public access

Scope dataset

DQ Completeness Commission

Effective date

2020-07-16

Explanation Water column imagery has been edited out of the dataset provided here but available

upon request

DQ Completeness Omission

Effective date

2020-07-16

Explanation

Where drop-outs of GPS positioning of the tow fish occurred, an interpolated value was calculated as described in the Lineage statement above. Forward looking video and recorded tow-fish parameters (i.e. roll/pitch/heave) are also available but not provided with this digital still dataset.

DQ Conceptual Consistency

Effective date

2020-05-18

Explanation

As the imagery is acquired using a moving platform some images may or may not capture part of the same section of seabed in subsequent images. Survey speed of ~ 1 kt (0.51m/s); image capture rate 1 image every 2 seconds; and approximate area of seabed captured in each image (0.5 - 2m2); 2 laser pointers denote a horizontal distance of 10cm where visible. nb: tow-fish roll, pitch and heave values are recorded by the video camera and saved within the video data file.

DQ Absolute External Positional Accuracy

Effective date

2020-05-18

Explanation

XY position of fish is determined by relative position of USBL transponder (fish) to transceiver (vessel). GPS position is G2 quality (<0.4-0.5m XYZ in realtime equiv. RTK) and is relative to the vessels Centre of Mass (reference frame 0:0:0) with a 2.4m forward offset (X = -1.5) from transceiver to COM entered in the USBL software (Y = 0). USBL heading offset is checked following each installation (nominally 23 degrees from centreline) and USBL (Tracklink, USA) precision is 3 degrees of slant range value. Original still image time-stamping is synched with computer UTC (<1s) but image naming convention utilises USBL/Video text feed based on POS MV time ss:mm:hh dd:mm:yyyy (UTC) output. The Tracklink USBL system suffers from drop outs (noise, power) for fish positioning and so when dropouts occurred the following protocol was followed when processing and interpolating positioning data: 1. Extract raw USBL data and partition into transects: interpolate (running average) where gaps are <10s: marked as FLAG 1 in the metadata file; 2. Extract GPS and Fish position (and other data) aligned with timestamps for each image (image to USBL time offset <1s); 3. Import ship and fish positions into Arc, then identify outlier points using 4m radius filter for successive UBSL fish position fixes; delete values and interpolate (running average) where gap is <10s; mark as FLAG 1 in metadata file. 4. Determine a median and SD of layback for true fish fixes and generate new fish position values over periods of 10s and as calculation of the new fish position relies on the last fish position there is likely to be an increase in positional error for the assumed fish-position over time. To rectify this, we applied an incremental (linear) offset/adjustment to ensure that the end of the 'drop-out' period aligned with next available USBL fish position in the sequence (i.e. when USBL positioning returned); marked as FLAG 3.

DQ Non Quantitative Attribute Correctness

Effective

date

2020-07-16

Explanation No non-quantitative attributes are provided here

Responsible party

Contact position Data Broker

Organisation name NSW Department of Climate Change, Energy, the Environment and Water

Telephone number 131555

Email address <u>data.broker@environment.nsw.gov.au</u>

Web address https://www.nsw.gov.au/departments-and-agencies/dcceew

Responsible party role pointOfContact

Metadata point of contact

Contact position Data Broker

Organisation name NSW Department of Climate Change, Energy, the Environment and Water

Telephone number 131555

Email address <u>data.broker@environment.nsw.gov.au</u>

Web address https://www.nsw.gov.au/departments-and-agencies/dcceew

Responsible party role pointOfContact

Metadata date 2024-02-26T12:54:41.998014

Metadata language